




## INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

<b>(51) International Patent Classification <sup>7</sup> :</b> <b>H04N 7/173</b>		<b>A1</b>	<b>(11) International Publication Number:</b> <b>WO 00/42768</b>
			<b>(43) International Publication Date:</b> 20 July 2000 (20.07.00)
<b>(21) International Application Number:</b> PCT/US00/00017 <b>(22) International Filing Date:</b> 14 January 2000 (14.01.00) <b>(30) Priority Data:</b> 09/231,283                      15 January 1999 (15.01.99)      US 09/232,750                      15 January 1999 (15.01.99)      US <b>(71) Applicant:</b> RESPOND TV, INC. [US/US]; 1083 Mission Street, San Francisco, CA 94103 (US). <b>(72) Inventors:</b> KAISER, David, H.; 2835 Ralston Avenue, Hillsborough, CA 94010 (US). LASH, Todd; 6668 Colton Boulevard, Oakland, CA 94611 (US). WEBER, Jay, C.; 302 Pope Street, Menlo Park, CA 94025 (US). <b>(74) Agent:</b> DONNELLY, Darren, E.; McCutchen, Doyle, Brown & Enersen, LLP, Three Embarcadero Center, San Francisco, CA 94111 (US).		<b>(81) Designated States:</b> AE, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, CA, CH, CN, CR, CU, CZ, DE, DK, DM, EE, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, NO, NZ, PL, PT, RO, RU, SD, SE, SG, SI, SK, SL, TJ, TM, TR, TT, TZ, UA, UG, UZ, VN, YU, ZA, ZW, ARIPO patent (GH, GM, KE, LS, MW, SD, SL, SZ, TZ, UG, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, CH, CY, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GW, ML, MR, NE, SN, TD, TG).  <b>Published</b> <i>With international search report.          Before the expiration of the time limit for amending the claims and to be republished in the event of the receipt of amendments.</i>	

**(54) Title:** SYSTEM ALLOWING SELECTION OF PRODUCTS IN A VIDEO PRODUCTION BY USING REFERENCE IMAGES**(57) Abstract**

Disclosed are a method, apparatus and system for providing action selections to an image referencing a product in a video production and a content reference architecture beneficially used therewith. According to the disclosure a method for providing action selections to an image referencing a product in a video production includes (1) communicating a video production to a reproducing apparatus, the video production comprising a placement zone and a trigger zone at least partially coincident with the placement zone, wherein the trigger zone comprises a trigger resource identifier, and wherein the placement zone comprises an image referencing a product; (2) communicating to the reproducing apparatus an indication that an action

selection interface associated with the product is available in response to a request corresponding to the trigger; and (3) communicating to the reproducing apparatus a characterization of the action selection interface, wherein the action selection interface comprises a selectable action. A disclosed method includes receiving a first request (URI) from a reproducing apparatus, for example a set-top box, the first request having been extracted from a video production communicated to the reproducing apparatus; determining a second resource identifier (URL) responsive to the first request and redirecting the first request wherein a response is provided to the reproducing apparatus.



**FOR THE PURPOSES OF INFORMATION ONLY**

Codes used to identify States party to the PCT on the front pages of pamphlets publishing international applications under the PCT.

AL	Albania	ES	Spain	LS	Lesotho	SI	Slovenia
AM	Armenia	FI	Finland	LT	Lithuania	SK	Slovakia
AT	Austria	FR	France	LU	Luxembourg	SN	Senegal
AU	Australia	GA	Gabon	LV	Latvia	SZ	Swaziland
AZ	Azerbaijan	GB	United Kingdom	MC	Monaco	TD	Chad
BA	Bosnia and Herzegovina	GE	Georgia	MD	Republic of Moldova	TG	Togo
BB	Barbados	GH	Ghana	MG	Madagascar	TJ	Tajikistan
BE	Belgium	GN	Guinea	MK	The former Yugoslav Republic of Macedonia	TM	Turkmenistan
BF	Burkina Faso	GR	Greece	ML	Mali	TR	Turkey
BG	Bulgaria	HU	Hungary	MN	Mongolia	TT	Trinidad and Tobago
BJ	Benin	IE	Ireland	MR	Mauritania	UA	Ukraine
BR	Brazil	IL	Israel	MW	Malawi	UG	Uganda
BY	Belarus	IS	Iceland	MX	Mexico	US	United States of America
CA	Canada	IT	Italy	NE	Niger	UZ	Uzbekistan
CF	Central African Republic	JP	Japan	NL	Netherlands	VN	Viet Nam
CG	Congo	KE	Kenya	NO	Norway	YU	Yugoslavia
CH	Switzerland	KG	Kyrgyzstan	NZ	New Zealand	ZW	Zimbabwe
CI	Côte d'Ivoire	KP	Democratic People's Republic of Korea	PL	Poland		
CM	Cameroon	KR	Republic of Korea	PT	Portugal		
CN	China	KZ	Kazakstan	RO	Romania		
CU	Cuba	LC	Saint Lucia	RU	Russian Federation		
CZ	Czech Republic	LI	Liechtenstein	SD	Sudan		
DE	Germany	LK	Sri Lanka	SE	Sweden		
DK	Denmark	LR	Liberia	SG	Singapore		
EE	Estonia						

## SYSTEM ALLOWING SELECTION OF PRODUCTS IN A VIDEO PRODUCTION BY USING REFERENCE IMAGES

**BACKGROUND**5       ***FIELD***

The invention relates generally to enhanced video more particularly to video operable with networked action resources and also to the handling of resource identifiers used in connection with enhanced video.

***BACKGROUND***

10       Enhanced Video including Enhanced Television involves a developing set of technologies directed towards providing viewers rich and customizable interaction options in connection with elements of a video production. Conventional means of providing the enhancing interactive content involve integrated devices capable of receiving and reproducing the video production and of interactive communications with resources available over a data  
15       network.

Purveyors of products generally wish to make information relating to their products available to prospective purchasers. It is particularly desirable to provide interactive information about a product. Interactive information allows a prospective purchaser to better receive desired information about a product, participate in interactive events respecting the  
20       product, and, of course, purchase the product. Typically interactive information also provided the added convenience to prospective purchasers of not having to transcribe access information in connection with product purchases.

At a minimum, however, purveyors of products frequently wish to make an image referencing their product present in a video production. It is frequently desired that the  
25       purveyor be able to select appropriate contexts in the video production for display of an image referencing their product in order develop or maintain the distinctive quality of the image referencing their product(s) and promote contextually-driven positive associations with their product(s). Both qualitative and quantitative factors are frequently contextually

relevant. Conventionally, purveyors of products arrange with authors of a video production to include a "product placement" in the video production. However, conventional product placements are unable to support interactive behavior.

A related technique for providing interactive behavior in a video production is to  
5 display a locator for a networked resource in a video production as is described, for example, in U.S. Patent 5,774,666 issued to Portuesi. Techniques similar to this may not provide a desired level of consumer acceptance in practice. Display of a locator for a networked reference may unnecessarily clutter a viewer's display. In addition, the locator may be unrecognizable by a viewer as being associated with any particular subject matter displayed  
10 on the viewer's display because of the frequently lengthy and confusing syntax of uniform network resource locators. A variation of this technique is to use so-called "hot spots." However this, too, only provides active regions on a display and a viewer may need to consult the uniform network resource locator displayed when the hot spot is active which, again, are frequently lengthy and confusing to understand, and needlessly distracting. Rather it would  
15 be desirable to have a solution in which images easily recognizable by a viewer as referencing a product could be used.

Another conventional solution is to provide a video production dedicated to providing information about a product. This solution may be unsatisfactory for several reasons. First it may be excessively costly. Creation of the video production dedicated to providing  
20 information about a product requires all the costs incurred in producing any video production which will be far beyond the resources of many vendors. Furthermore, when as brief as a conventional commercial, it is of insufficient duration to support rich or involved interactive features which may be a necessity to effectively compete in the marketplace. Second, this solution is frequently deficient in reaching a wide audience of prospective purchasers.  
25 Typically, the audience of the video production dedicated to providing information about a product is limited to a small segment of the potential market for who the opportunity cost of viewing the dedicated video production is quite low. By contrast, video productions of

primarily entertainment value can draw large audiences. Third, there is limited availability for commercially desirable broadcasting times for a video production dedicated to providing information about a product as the commercially desirable broadcasting times conventionally are reserved for video productions of primarily entertainment value. Using conventional  
5 interactive television techniques with the video production dedicated to providing information about a product cannot eliminate these drawbacks.

It is therefore desirable that a system and method exist that allows interactive product behavior to be provided to an image referencing a product in a video production, that provides purveyors with the flexibility to select contextually appropriate segments of a video  
10 production for interactive behavior, that operates with images referencing products and other symbols easily recognizable by a viewer, that is cost effective, and that operates with video productions of the type conventionally found in commercially desirable time slots.

Given the high rate of television ownership, consumer familiarity with, and appreciation of, television, conventional Enhanced Video solutions frequently operate with  
15 widely used television broadcast signals. Such solutions typically involve encoding one or more resource identifiers into non-viewed portions of the television broadcast signals. The resource identifiers are then extracted by an integrated device which then presents to the viewer in some manner the option of interacting with enhancing resources available via the resource identifier.

20 Frequently, the resource identifiers are encoded in the vertical blanking interval ("VBI") of a television broadcast signal. An industry standard provided from the Electronic Industries Association ("EIA") of Arlington, VA, U.S.A. defines a system for the transport of internet Uniform Resource Locator ("URL") information using the Text-2 service of line 21 of the VBI.

25 The EIA standard syntax provides that the general format for transport of URL information in the VBI is to provide the URL followed by zero or more pairs of attributes and

values which is then followed by a checksum. The EIA standard further indicates that, in order to preserve sufficient bandwidth for other services that use line 21 of the VBI, URL information should be limited.

Limitation on URL information can be inconvenient. While resource identifiers, including URLs, can be compact, it may be desirable that they be quite lengthy. For example, GET-based forms in compliance with the Hypertext Transfer Protocol ("HTTP") commonly involve URLs that are quite lengthy. It may also be desirable to include numerous parameter-parameter value pairs in a resource identifier to provide greater customization of interactions. It is therefore desirable that a solution exist that allows enhancing content customization through use of lengthy or parameterized resource identifiers without consuming limited bandwidth in a video production.

Another problem that arises in connection with Enhanced Video is synchronization of the content of the video production with the enhancing content. This may take on many forms. Some examples are created by the passage of time between creation of the video production and the time when enhancing interaction is desired. For example, a television program may be originally created with encoded resource identifiers to enhancing content relating to a promotion for the latest model of a vendor's product. After the passage of time, for example when the program were broadcast again as a re-run the following year, the resource identifier may no longer address the vendor's latest product because newer versions may have been released during the intervening time period. The same type of problem can arise in the context of an instructional video production. For example, the originally created encoded resource identifiers may address the scholarship, regulations, or additional instructional content appropriate at the time the video production was created. However after the passage of time, these same resource identifiers could provide enhancing content that was misleading. It would thus be advantageous that a solution exist that allows for time-appropriate enhancing content to be provided in connection with an enhanced video production.

A different time-related synchronization problem that may arise in connection with Enhanced Video stems from an inability to provide resource identifiers to appropriate enhancing content by the time for broadcast of the video production; for example, a live video feed from a sporting or news event. As the event unfolds, opportunities may arise where it would be desirable to provide enhancing content. However, it is may be impossible to predict all contingencies for which it would be desirable to provide opportunistic enhancing content. For example, during a baseball game a triple play may occur and it may be desirable to provide enhancing content about other triple plays, statistics, and the like which are available in data storage of the broadcaster or an affiliated entity. However, it would impractical or burdensome to provide resource identifiers directly to these resources. Accordingly, it would be beneficial that a solution exist that allows for opportunistic provision of enhancing content.

Yet another problem that may arise in connection with Enhanced Video is that of appropriate internationalization. Video events frequently draw international audiences, for example, Olympic and other sporting competitions, space exploration, and international conflicts. The author or publisher of video productions of such events may desire to provide distinct enhancing content for different national, or linguistic groups. However it may be inconvenient or impossible to provide separate resource identifiers in the video production for each group. Therefore it would be favorable for a solution to exist that facilitates internationalization of enhancing content.

In connection with Enhanced Video, it is further desirable that a method and system exist for providing resource identifiers to support an enhanced video production in advance of having any enhancing content and/or in advance of an arrangement that a particular entity will provide enhancing content. For example, an author of a video production may desire to generate revenue by, for example, selling the rights to provide enhancing content in connection with one or more particular resource identifiers. Such an author would desire a method and system that would allow the author to embed resource identifiers in the author's

video production in a manner that would allow the author (or other entity holding appropriate rights) to sell the rights to provide enhancing content to one or several parties after creation of the video production. Conventional methods are unable to provide a solution to such an author in that typical resource identifiers specify a path that is dependent on the particular content associated with the resource identifier. Conventional redirection is also unable to provide a solution to such an author because the author may sell the rights to provide enhancing content to several different entities. Each of the several different entities would typically desire to have requests for enhancing content initiated in response to selection of a resource identifier for which the entity owned the right to provide enhancing content directed to the entity's server; conventional redirection is unable to provide a solution to this type of problem.

### **SUMMARY**

In order to provide these and other desired features, the instant invention provides a method and system for providing action selections to an image referencing a product in a video production and a content reference architecture that may beneficially used therewith.

A illustrative method in accordance with the invention may include: communicating a video production to a reproducing apparatus, the video production including a placement zone and a trigger zone at least partially coincident with the placement zone, wherein the trigger zone includes, at least, a trigger resource identifier, and wherein the placement zone includes an image referencing a product; communicating to the reproducing apparatus an indication that an action selection interface associated with the product is available in response to a request corresponding to the trigger; and communicating to the reproducing apparatus a characterization of the action selection interface, wherein the action selection interface comprises a selectable action. Such a method may further include: receiving an indication of the selection of the selectable action; retrieving an action resource associated with the selectable action; and communicating the action resource to the reproducing



apparatus. The action resource may be selected responsive to a profile of a user associated with the reproducing apparatus.

The video production may be provided in several ways including, for example, communicated over a television network, distributed in a tangible medium, or transferred  
5 over a computer network.

The indication of the action selection interface may take many forms including, for example, a visual highlight. In some illustrative methods, when the reproducing apparatus is coupled to a viewing device, the visual highlight is communicated to the viewing device only if the reproducing apparatus supports the action selection interface.

10 Selectable actions for use with a conforming method include for example, a product purchase action, a promotion participation action, or an information request action.

A method for creating a video production including a placement zone and a trigger zone and comprising an image referencing a product and having a selectable action available for communication to a reproducing apparatus according to the invention may include:  
15 selecting a placement zone in a video production, the placement zone comprising an image referencing a product; selecting a trigger zone in the video production corresponding to the placement zone; embedding a reference in the trigger zone in said video production to an action selection interface, wherein when reproduced on compatible equipment and communicated to a display, a selectable action in the action selection interface is selectable by  
20 a viewer. The video production may include a first track including the trigger zone and a second track including the placement zone, wherein the first and second tracks are synchronized.

An apparatus with a processor, a memory, and an input-output system and configured for communication with a reproducing apparatus via a data network may also embody aspects  
25 of the invention. Programmed instructions may configure the apparatus to perform a method

including receiving a request from a reproducing apparatus, said request corresponding to a trigger from a trigger zone in a video production communicated to the reproducing apparatus; determining whether an action selection interface associated with said request is available; and communicating a characterization of the action selection interface to the reproducing  
5 apparatus.

A system for providing action selections to an image referencing a product in a video production and operable for use with a reproducing apparatus configured for communication with a display, a data network, and a selection device is another aspect of the invention. The system may include a video production communication device, that can communicate a video  
10 production comprising a placement zone and a trigger zone to the reproducing apparatus; and an action resource provider configured for communication with the reproducing apparatus via the data network, the action resource provider receiving a request from the reproducing apparatus corresponding to a trigger in the trigger zone of the video production, the action resource communicating a characterization of an action selection interface to the reproducing  
15 apparatus responsive to the request, the action selection interface comprising a selectable action. In such a system, the action resource provider may further receive a request from the reproducing apparatus corresponding to the selectable action; retrieve an action resource associated with the selectable action; and communicate an action resource associated with the selectable action to the reproducing apparatus.

20 Other aspects of our invention provide a method, apparatus, and system for indexical content references in enhanced video productions.

A method for indexical content references in accordance with the invention may include: receiving a first request from an integrated enhanced video device (the first request including a first resource identifier and the first resource identifier is extracted from a video  
25 production provided to the enhanced video device); also, determining a second resource identifier in response to the first resource identifier; and also, redirecting the first request to

the second resource identifier; and thereafter a response is sent to the integrated enhanced video device. In accordance with such a method, determining a second resource identifier may include: identifying at least one parameter; also, identifying at least one parameter value associated with the at least one parameter; and also, determining a second resource identifier  
5 that includes the parameter(s) and parameter value(s) in response to the first resource identifier. In accordance with such a method, determining a second resource identifier may include: identifying a parameter of a first type and a parameter of a second type (the parameter of a second type identified in response to a header in the request); and also, identifying a first parameter value associated with the parameter of a first type and a second  
10 parameter value associated with the parameter of a second type (the first parameter value is identified in response to an expression associated with the header). In accordance with such a method, redirecting the first request may be either an internal redirection or an external redirection; if external, it may be to a separate server or to the enhanced video device.

Another aspect of the invention is a system that may include: a video production  
15 communication device; also, an enhanced video device configured to receive a video production from the video production communication device (the video production including, a first resource identifier) and send a request including the resource identifier via a data network; also, a first server communicating via the data network, the first server configured to receive the request, determine a second resource identifier, and redirect the request to the  
20 second resource identifier. Such a system may also include a second server, and the second resource identifier may be addressable via the second server.

An illustrative apparatus in accordance with the invention and including, at least, a processor, a storage, and an-input output system may be a programmed computer. Programmed instructions may configure the computer to provide special purpose computing  
25 machinery including a first request receiver for receiving a first request from a reproducing apparatus, said first request comprising a first resource identifier, said first resource identifier extracted from a video production communicated to said reproducing apparatus; a second

resource identifier determiner for determining a second resource identifier responsive to said first resource identifier; and a first request redirector for redirecting said first request to said second resource identifier, wherein thereafter a response is communicated to said reproducing apparatus. The second resource identifier determiner may included, at least, a parameter  
5 identifier for identifying a parameter; a parameter value identifier for identifying a parameter value associated with said parameter; and a second resource identifier determiner for determining a second resource identifier comprising said parameter and said parameter value responsive to said first resource identifier. The second resource identifier determiner may include a parameter identifier for identifying a parameter of a first type and a parameter of a  
10 second type, wherein said parameter of a first type is identified responsive to a header in said first request; and a parameter value identifier for identifying a first parameter value associated with said parameter of a first type and a second parameter value associated with said parameter of a second type, wherein said first parameter value is identified responsive to an expression associated with said header. The first request redirector may be an internal  
15 redirector or an external redirector. If an external redirector, an external redirect message may be sent to the reproducing apparatus.

Another aspect of the invention are methods of creating a video production including indexical content references. An illustrative one includes: selecting an indexical reference corresponding to a resource identifier addressable on a data network; determining a reference  
20 location in a video production; and encoding said indexical reference at said reference location in said video production, wherein when said video production is reproduced on a compatible reproducing apparatus, said reproducing apparatus communicates a first request to said resource identifier, a server addressable via said resource identifier generates a current content reference, a second request is sent to said current content reference, and responsive to  
25 said second request information is communicated to said reproducing apparatus.

An additional aspect of versions of the invention provides a system for encoding one or more series of resource identifiers in a video production. An illustrative system includes:

an encoding controller; a video production player, operation of the video production player under control of the encoding controller; a resource identifier encoder, the resource identifier encoder configured to receive an input video signal from the video production player, the resource identifier encoder further configured to encode resource identifiers in the input video signal in response to encoding instructions from the encoding controller and provide an output video signal comprising the input video signal and the resource identifiers; and a video production recorder, operation of the video production recorder under control of the encoding controller, the video production recorder receiving the output video signal and storing said output video signal in a storage medium.

Yet another aspect of the invention provides a method for encoding one or more series of resource identifiers in a video production. A illustrative method includes: receiving a first starting position for a first series; receiving a first encoding pattern for the first series; embedding a first resource identifier at the first starting position; and embedding the first series of one or more resource identifiers in the video production in accordance with the first starting position. Such a method may further include: receiving a second starting position for a second series; receiving a second encoding pattern for the second series; embedding a second resource identifier at the second starting position; and embedding the second series of one or more resource identifiers in the video production in accordance with the second starting position. Encoding patterns in such methods may be fixed intervals. Resource identifiers in series may be identical.

### **BRIEF DESCRIPTION OF THE DRAWINGS**

These and other features, aspects, and advantages of the present invention will become better understood with regard to the following description, appended claims, and accompanying drawings where:

Fig. 1 is a block diagram showing elements used with a system for providing action selections to an image referencing a product in a video production in accordance with an illustrative embodiment;

5 Fig. 2 depicts a video production with placement zones and trigger zones in accordance with an illustrative embodiment;

Fig. 3 depicts a reproducing apparatus in accordance with an illustrative embodiment;

10 Fig. 4 depicts a flow diagram for a method of creating a video production including a placement zone and a trigger zone and comprising an image referencing a product and having a selectable action available for communication to a reproducing apparatus in accordance with an illustrative embodiment;

Fig. 5 depicts a flow diagram for a method of providing action selections to an image referencing a product in a video production in accordance with an illustrative embodiment;

15 Fig. 6A depicts a displayed view of an indication that an action selection interface is available in accordance with an illustrative embodiment;

Fig. 6B depicts a displayed view of a visual highlight as an indication that an action selection interface is available in accordance with an illustrative embodiment;

20 Fig. 6C depicts a displayed view of a rendered characterization of an action selection interface in accordance with an illustrative embodiment;

Fig. 6D depicts a displayed view of a rendered characterization of an action selection interface in accordance with an illustrative embodiment;

Fig. 7 depicts a flow diagram for a method of implementing a promotion participation action in accordance with an illustrative embodiment;

Fig. 8 depicts a flow diagram for a method of implementing a information request action in accordance with an illustrative embodiment;

5 Fig. 9 depicts a flow diagram for a method of implementing a product purchase action in accordance with an illustrative embodiment; and

Fig. 10 depicts a computer system capable of being configured to embody aspects of the invention in accordance with an illustrative embodiment.

10 Fig. 11 depicts a flow diagram for a method of creating a video production including indexical content references in accordance with an illustrative embodiment;

Fig. 12 is a block diagram of elements in an operating environment of an illustrative embodiment;

15 Fig. 13 depicts a flow diagram of a method for providing indexical triggers in an enhanced video production;

Fig. 14 depicts a flow diagram of a method for a second URI generation procedure;

Fig. 15 depicts a block diagram of a system for encoding one or more series of resource identifiers in a video production in accordance with an illustrative embodiment; and

20 Fig. 16 depicts a flow diagram of a method for encoding one or more series of resource identifiers in a video production in accordance with an illustrative embodiment.

## DETAILED DESCRIPTION

### **NOTATIONS AND NOMENCLATURE**

- (1) `http://<server name>/<videoprod>/<position>`  
(2) `http://<server name>/p/<project>/<name1>=<value1>/<name2>=<value2>/<name3>=/start.html`

Action Selection Interface is abbreviated “ASI”

“Product.” As used herein, the term “product” includes, at least, goods, services, collective entities, and certifications.

### **DESCRIPTION OF FIGURES**

While this invention is susceptible of embodiment in many different forms, there are  
5 described herein in detail illustrative embodiments with the understanding that the present disclosure is to be considered as an example of the principles of the invention and is not intended to limit the invention to the embodiments illustrated.

Fig. 1 shows a block diagram of the system elements **1000** used in conjunction with an illustrative embodiment. In operation, a video production **1100** is provided to a video  
10 production communicating device **1800** which communicates the video production **1100** to a reproducing apparatus **1300**. The video production **1100** is described in greater detail in connection with **Fig. 2** and the reproducing apparatus **1300** is described in greater detail in connection with **Fig. 3**.

The video production **1100** may be in a tangible medium, including, for example,  
15 video tape, video disc, or digital video disc (DVD). In some embodiments the video production **1100** is transferred over a computer network. The video production **1100** could be streamed or all, or substantially all, of a file comprising the video production **1100** could be transferred before reproduction begins.



The video production communicating device **1800** generates an output operable with the reproducing apparatus **1300** from the video production **1100**. For example, if the video production **1100** were by DVD, the video production communicating device **1800** could be a conventional DVD player; if the video production **1100** were transferred over a computer network, the video production communicating device **1800** could be a programmed computer. In some embodiments the video production communicating device **1800** may be a broadcast station, either terrestrial or orbiting. One of skill in the art will recognize which structures, for example the DVD player or programmed computer, are suitable to operate with the video production **1100** depending on its form.

In an illustrative embodiment the video production **1100** is communicated to the reproducing apparatus **1300** with a broadcast network and the video production communicating device **1800** is conventional broadcasting hardware. In a more preferred embodiment the broadcast network is a television network; in a still more preferred embodiment, the video production is broadcast as a National Television Standards Committee (“NTSC”) video signal; PAL, SECAM, or high-definition television formats could also be used.

Generally, the reproducing apparatus **1300** is capable of receiving the video production communicated by the video production communicating device **1800** and reproducing an video signal comprising the video production to, for example, a display **1200**. In addition, generally, the reproducing apparatus **1300** may operate as a client in client-server communications. Also, a selection device **1700** typically operates with the reproducing apparatus **1300** and allows a user (not shown) to select among selectable actions rendered on the display **1200**. As one of skill in the art will recognize, the particular form that the selection device **1700** takes may vary with the reproducing apparatus **1300**.

The reproducing apparatus **1300** communicates over a data network **1400**. The data network **1400** may be the same or a separate transmission medium as that through which the

video production communicating device **1800** communicates the video production **1100** to the reproducing apparatus **1300**, including, for example, a computer network or broadcast. In the illustrative embodiment, the data network is the internet; preferably the hypertext transfer protocol (HTTP) is used. The data network **1400** may, more generally, include other forms of data communication.

Configured for communication with the reproducing apparatus **1300** via the data network **1400** is an action resource provider **1500**. The action resource provider **1500** provides action resource data to the reproducing apparatus **1300**. Action resource data, generally, may include instructions, such as HTML, XML, or SGML pages; scripts, programs, and analogous instructing informational languages which when parsed and rendered on suitable equipment provide for interaction. Typically action resource data includes a characterization of an interface. The interface results from suitable equipment parsing and rendering the characterization. In an illustrative embodiment, the action resource provider **1500** is an HTTP server. However, one skilled in the art will appreciate that the action resource provider **1500** could be other devices capable of communicating action resources with which the reproducing apparatus **1300** is configured to operate. In the illustrative embodiment the action resource provider **1500** communicates with a data storage **1600**. The data storage **1600** may store, for example, user profile data, product data, merchant data logs, or program guides.

**Fig. 2** depicts a representation of a video production **1100**. Shown are a first placement zone **1110**, a second placement zone **1130**, and a Nth placement zone **1150** which correspond, respectively, to a first trigger zone **1120**, a second trigger zone **1140**, and a Nth trigger zone **1160**. The video production **1100** is not limited in the number of placement zones or trigger zones and N may be arbitrarily large or small. The trigger zones need not be precisely coincident with the placement zones.

In an illustrative embodiment, a placement zone comprises one or more frames of a video production, the one or more frames comprising an image referencing a product. The number of frames in the placement zone is not limited other than relative to the video production itself. As depicted in **Fig. 2**, the first placement zone **1110**, the second placement zone **1130**, and the Nth placement zone **1150** are disjoint. However, this is not fundamental to the invention and, for example, the first placement zone **1110** and the second placement zone **1130** could overlap. In the case of an overlap, plural products could be referenced by the image or images. One skilled in the art will further appreciate that a conventional video production may have one or more placement zones inherent in its layout while, also, placement zones may be added to a conventional video production using well-known editing techniques.

Within a trigger zone, for example, the first trigger zone **1120** are one or more triggers. In an illustrative embodiment, triggers are compliant with the CEMA EIA-746 standard or analogous standard. A trigger comprises a resource identifier. In the illustrative embodiment, the resource identifier is a Uniform Resource Identifier (URI) of the form:

http://<server name>/<videoprod>/<position> (1)

The material denoted within angle-brackets < > are denote names of quantities used in accordance with an illustrative embodiment. In (1) above, <server name> may be any server addressable on the data network **1400**, including, for example, the action resource provider **1500**, conveniently, the server may be a dedicated server. <videoprod> refers to an identifier of the video production **1100** (or a segment thereof) into which a trigger is embedded. Conveniently, the <videoprod> is not temporally unique. i.e., the video production and embedded trigger may be distributed at arbitrary or multiple times. Triggers may also be indexical as described below in the section titled Indexical Content References. <position> refers to a position within the video production **1100**, exemplary positions may be the first trigger zone **1120** or the Nth trigger zone **1160**. In the illustrative embodiment, positions may

be either temporally indexed or indexed by segments of the video production **1100**. More generally, a trigger resource identifier could identify other resources addressable in a client-server data communications network.

Conveniently, a trigger may be embedded in the Text-2 service of line 21 of the  
5 Vertical Blanking Interval of an analog television signal as specified in CEMA standard EIA-746 available from The Electronic Industries Association of Arlington, Virginia, U.S.A.. Conventional closed-captioning equipment may be used to embed triggers in accordance with the CEMA standard.

One aspect of the invention is the portion of the video production **1100** which is  
10 spanned by placement zones or trigger zones. Conventionally, many video productions are viewed primarily for entertainment purposes. It is undesirable for one or more images referencing one or more products to be the dominant images or dominant subject matter in a video production viewed for such purposes. In such a situation, a viewer of the video production may find non-dominant images of insufficient interest to retain viewership,  
15 possibly frustrating viewer expectations and forgoing the possibility of selection of selectable actions from an action selection interface made available through the video production.

In one embodiment of the invention the placement zones for a given product in a video production according to the invention are less than 50 % of the viewable time of the video production. Alternative embodiments may use, for example, less than 40%, 33%, 25%,  
20 20%, 10%, or 5%. A placement zone may span a single segment in a video production. Shares of the total viewable time of the video production corresponding to one of a number of segments may thus also be used, including, for example (1/6) or about 15%. As one of skill in the art will appreciate having the benefit of this disclosure, a placement zone according to the invention will have some portion of the viewable time of the video production.

25 The video production **1100** operates with the reproducing apparatus **1300** which described in greater detail below with reference to **Fig. 3**. As noted above, the reproducing

apparatus **1300** provides, at least, the functions of receiving and reproducing the video production and of a client in client-server communications. One of skill in the art will recognize numerous structures of programmed or programmable logic also capable of performing these and other functions in accordance with aspects of the invention. Exemplary structures could include, for example, a programmed general purpose computer with suitable video hardware, an integrated receiver/client appliance such as a set-top box, and special purpose computing machinery comprising an application specific integrated circuit (ASIC). Structures currently commercially available which provide at least the above-identified functions include, for example, a WEBTV Plus set-top box available from WebTV Networks, Inc. of Palo Alto, CA, U.S.A. It is contemplated, however, that the present invention will operate with other structures able to perform the above-identified functions (now known or later-developed). The remote control used with the WEBTV Plus set-top box is one example of a suitable form for the selection device **1700**. Many others will be recognized by those of skill in the art including, for example, pointing devices used with personal computers, other selection systems such as those based on speech recognition, and touch-screen systems.

One of skill in the art will recognize other features incorporated in set-top boxes with which aspects of the invention may operated. Other features may include, for example, a card reader (not shown). The card reader may read identification or financial information cards and the identification or financial information may be used with selectable actions according to the invention. The card reader may work with smart cards, and stored-value cards; in embodiments in which a selectable action includes transfer of value. The card reader may be used to read information from a card for payment of value.

Preferably, the reproducing apparatus **1300** communicates with the display **1200** and the data network **1400**. In operation, the video production communicating device **1800** communicates the video production **1100** to the reproducing apparatus **1300**. A trigger interpreter **1330** interprets triggers in the video production **1100** such as those in the second trigger zone **1140** or the Nth trigger zone **1160**. The trigger interpreter **1330** sends a request

1340 via the data network 1400. The request 1340 is received by the action resource provider 1500. The request 1340 may be handled as described in the section below entitled "Indexical Content References". If an action selection interface is available for the particular trigger, an ASI indication 1360 is communicated via the data network 1400 to the reproducing apparatus 1300. An Response interpreter 1320 parses the ASI indication 1360 and communicates a visual indication of the ASI indication 1360 to a content integrator 1310. The content integrator 1310 integrates the visual portions of the video production 1100 and visuals from the Response interpreter 1320; the integrated visual may then be communicated to the display 1200.

10           When an ASI characterization 1380 is available for a particular trigger, it is communicated via the data network 1400 to the Response interpreter 1320 in the reproducing apparatus 1300 as well. The Response interpreter 1320 parses the ASI characterization 1380 and renders a visual representation thereof which is communicated to the content integrator 1310 for communication to the display 1200.

15           In an illustrative embodiment of the invention the indication of the availability of an ASI is one which is rendered as a visual image on the display 1200. In other embodiments the indication of the availability of an ASI may be audio. In still other embodiments, it may not be communicated to the display 1200. More, generally, the indication of the availability of an ASI may be a portion of the characterization of the ASI itself. In embodiments of the invention where the action resource provider 1500 is an HTTP server using the HTTP protocol, the indication of the availability of an ASI may be, for example, all, or a portion, of an HTTP Response Message sent after the action resource provider 1500 received and interpreted an HTTP Request Message.

25           The ASI characterization 1380, generally, provides a characterization of an interface which may be parsed and rendered by the reproducing apparatus 1300 to provided one or more selectable actions. Preferably, the ASI characterization 1380 is also communicated

using the HTTP protocol and the ASI characterization **1380** is preferably an HTML page which, typically, includes HTML extension tags for use with interactive television. One method of providing selectable actions is to provided links to action resources. However, the selectable actions may be implemented using other conventional client-side or client-server techniques. Action resources may be implemented using well-known programming methods. Conveniently, internet programming methods may be used and an action resource may be implemented with, for example, HTML pages, XML pages; CGI scripts or programs, servlets or other server-side scripts or programs; client-side scripts, applications or applets, or active controls; and other client-server methodologies. One of skill, having the desired functions of the action resource, will apprehend how it could be made or used with conventional programming methods.

**Fig. 4** depicts a flow diagram of a ‘reference embedding’ method **4000** in accordance with the illustrative embodiment. From a ‘start’ terminal **4100** processing continues to a ‘video production selection’ procedure **4200**. The ‘video production selection’ procedure **4200** entails selecting a video production, such as the video production **1100**. Preferably, the video production **1100** already contains one or more images referencing one or more products, however, the additional step of embedding one or more images referencing one or more products may be performed using conventional video editing methods. Next an ‘ASI location selection’ procedure **4300** is entered in which locations, such as the second placement zone **1130** or the Nth placement zone **1150** are selected as locations in the video production **1100** where action selection interfaces are desired to be provided. Then, an ‘ASI reference embedding’ procedure **4400** commences in which a reference to an action selection interface is embedded in the video production **1100** at, for example, the second trigger zone **1140** or the Nth trigger zone **1160**. In an illustrative embodiment, the reference is a trigger such as that described above.

Process flow continues to an ‘additional locations’ decision procedure **4500**. If it desired to select additional locations in the video production **1100** at which action selection

interfaces could be made available, the 'additional locations' decision procedure **4500** exits through its 'yes' branch and process flow returns to the 'ASI location selection' procedure **4300** for another iteration. Otherwise, the 'additional locations' decision procedure **4500** exits thorough its 'no' branch and the 'reference embedding' method **4000** completes  
5 through an 'end' terminal **4600**.

Shown in **Fig. 5** is a flow diagram of a 'viewer action session' method **5000** in accordance with an illustrative embodiment. Process flow initiates at a 'start' terminal **5100** and continues to a 'video production communication' procedure **5200**. The 'video production communication' procedure **5200** involves communication of a video production such as the  
10 video production **1100** from the video production communicating device **1800** to the reproducing apparatus **1300**. During reproduction of the first trigger zone **1120** when a trigger is encountered the request **1340** is sent and an 'ASI indication communication' procedure **5300** executed by which the ASI indication **1360** is communicated to the reproducing apparatus **1300**. Next, an 'ASI characterization communication' procedure **5400**  
15 communicates the ASI characterization **1380** to the reproducing apparatus **1300**. The ASI characterization **1380** is parsed, rendered, integrated with other visuals, and communicated to the reproducing apparatus **1300**. A user (not shown) may then select one or more selectable actions from the action selection interface as displayed on the display **1200**. An 'action selection' decision procedure **5500** exits through its 'yes' branch if the user selects one of the  
20 selectable action and process flow continues to an 'action resource retrieval' procedure **5600**. In the 'action resource retrieval' procedure **5600** an action resource is retrieved from the action resource provider **1500** and communicated to the reproducing apparatus **1300** via the data network **1400** in an 'action resource communication' procedure **5700**. The Response interpreter **1320** parses and renders visuals aspects of the action resource. Next, an  
25 'additional actions' decision procedure **5800** exits through its 'yes' branch if the user selects additional actions and process flow returns to the 'action resource retrieval' procedure **5600**. If no action was selected in the 'action selection' decision procedure **5500** or if an additional



action is not selected in the 'additional actions' decision procedure **5800** process flow completes through an 'end' terminal **5900**.

A viewer's perspective of the display **1200** will now be provided to further illustrate aspects of the illustrative embodiment. Shown in **Fig. 6A** are the display **1200** and an image  
5 referencing a product **6100**. As noted above, the image referencing a product **6100** may refer either directly or indirectly to the product. Thus, for example, if the image referencing a product **6100** were an image of a car, the referenced product could be the car or, for example, car insurance services, car quality certification, or a car vending collective.

Also shown in **Fig. 6A** is a visual indication of the availability of an ASI **6200**. As  
10 noted above, the indication of the availability of an ASI may be rendered as a visual image on the display **1200** while in other embodiments the indication of the availability of an ASI may be in other forms. In accordance with the illustrative embodiment the visual indication of the availability of an ASI **6200** could be provided with an HTML page with television extension tags which render the video production **6600** in one portion of the display **1200**, and the  
15 visual indication of the availability of an ASI **6200** in another.

An alternative manner of providing the visual indication of the availability of an ASI **6200** is depicted in **Fig. 6B** where a visual highlight **6500** of the image referencing a product **6100** is shown. The visual highlight **6500** may be an image edited to highlight the image  
20 referencing a product **6100** which may be tracked through multiple frames of the video production **6600**. Conveniently the visual highlight **6500** may be implemented with an HTML table. The height and width of the table and its cells are suitably selected for the size of the visual highlight **6500** of the image referencing a product **6100**. An image providing the visual highlight **6500** is located in one cell of the table. In some embodiments, the height and width of the cell are adjusted to locate the upper left corner of the visual highlight **6500**  
25 image. As the image referencing a product **6100** moves during the video production, the upper left corner of the visual highlight **6500** may be made to track the image referencing a

product **6100** by adjusting the height and width of the cell in which the visual highlight **6500** is located. Accordingly, an additional aspect of some embodiments of the invention is a method for tracking an image in a video production with an overlay image.

5 In some embodiments of the invention the action resource provider **1500** detects if the reproducing apparatus **1300** is able to support a type of selectable action in an action selection interface from information in the request **1340** for example, a user-agent header field. In some of these embodiments the visual highlight **6500** is communicated to the reproducing apparatus **1300** only if the reproducing apparatus **1300** supports the selectable action in the action selection interface.

10 Shown in **Fig. 6C** and **Fig. 6D** are the display **1200**, the image referencing a product **6100** and a rendered characterization of an action selection interface **6300**. While the rendered characterization of an action selection interface **6300** is generically depicted, one of ordinary skill in the art will appreciate that it may be as complex as can be parsed and rendered by the reproducing apparatus **1300**. As depicted, the rendered characterization of an  
15 action selection interface **6300** comprises the plurality of selectable actions **6400** which may be selected by a user with, for example, the selection device **1700**. As shown in **Fig. 6C** the rendered characterization of an action selection interface **6300** appears in a portion of the display **1200** separate from the video production **6600**. However, as depicted in **Fig. 6D**, the rendered characterization of an action selection interface **6300** may appear in the same  
20 portion of the display **1200** as the video production **6600**. One skilled in the art will quickly appreciate that the views in **Fig. 6A**, **Fig. 6B**, **Fig. 6C**, and **Fig. 6D** are illustrative and not limiting, rather one of skill will be able to make and use other configurations of the elements in the aforementioned figures.

The selectable actions in the plurality of selectable actions **6400** may be any action  
25 susceptible to implementation in the action resource provider **1500** and the reproducing apparatus **1300**.

To further illustrate aspects of the invention, **Fig. 7**, **Fig. 8**, and **Fig. 9** depict methods for implementing exemplary selectable actions. One of skill in the art will quickly appreciate that these are illustrative and not limiting of the scope of the invention. Rather, one skilled in the art will recognize numerous other selectable actions operable with the invention.

5           One selectable action is a promotion participation action. Conveniently the promotion participation action is a link to action resources which implements the promotion participation action. Further illustrative detail of an may be found in **Fig. 7** where a promotion participation action method **7000** is depicted. Functions described in the promotion participation action method **7000** may be implemented with, for example, HTML  
10   pages, XML pages; CGI scripts or programs, servlets or other server-side scripts or programs; client-side scripts, applications or applets, or active controls; and other client-server methodologies. Processing initiates at a 'start' terminal **7100** and continues to a 'promotion information communication' procedure **7200** which communicates information about the promotion participation action to the reproducing apparatus **1300**. Next, a 'participant  
15   information receipt' procedure **7300** stores information communicated by a user of the reproducing apparatus **1300** relevant to participation in the promotion and processing continues to a 'participant registration' procedure **7400**. The 'participant registration' procedure **7400** completes the basic information exchange for a promotion participation which may involve data interchange with other servers (not shown), for example those  
20   operated by the promoting entity or affiliate. An 'additional participation' decision procedure **7500** allows a participant to select participation in additional aspects of the promotion. Additional participation options may be communicated to the reproducing apparatus **1300** which a user views on the display **1200**.

          If the user does not wish to engage in additional aspects of the promotion, the  
25   'additional participation' decision procedure **7500** exits through its 'no' branch and processing completes through an 'end' terminal **7900**. Otherwise, the 'additional participation' decision procedure **7500** exits through its 'yes' branch and a 'next page(s)

communication' procedure **7600** communicates one or more pages to the reproducing apparatus **1300** for the participant. A 'next information receipt' procedure **7700** receives additional information as necessary or desired from the participant and processing continues to a 'next participation action' procedure **7800** which performs one or more additional participation actions. These may include, for example, information exchange or storage with a promoting entity or affiliate. It may be desirable for additional participation options to be offered, and processing returns to the 'additional participation' decision procedure **7500** through which such additional participation may begin.

Another selectable action is a information request action. Conveniently the information request action is a link to action resources which implements the information request action. Further illustrative detail of an may be found in **Fig. 8** where an information request action method **8000** is depicted. Functions described in the information request action method **8000** may be implemented, for example, with HTML pages, XML pages; CGI scripts or programs, servlets or other server-side scripts or programs; client-side scripts, applications or applets, or active controls; and other client-server methodologies. Processing for the information request action method **8000** initiates at a 'start' terminal **8100** and continues to a 'information page(s) communication' procedure **8200** in which one or more pages are communicated to the reproducing apparatus **1300** for communication to the display **1200**. Commonly, plural informational options are presented to a user. A 'user input processing' procedure **8300** receives indication of user selections from the reproducing apparatus **1300** and performs any transformations convenient in extracting or reporting aspects of the user selections. In addition, the 'user input processing' procedure **8300** may also log, for example, user data or information request data. Then an 'information generation' procedure **8400** generates information output for reporting to the user. The 'information generation' procedure **8400** may employ any of many known report generation or extraction methods to produce the requested information for presentation to the user. An 'information communication' procedure **8500** then communicates requested information to the user. The requested information may be communicated to the user via the reproducing

apparatus **1300** and the display **1200** or be communicated through other methods including, for example, by post or facsimile. The information request action method **8000** completes through an 'end' terminal **8600**.

Another selectable action is a product purchase action. Conveniently the product  
5 purchase action is a link to action resources which implements the product purchase action. Further illustrative detail of an may be found in **Fig. 9** where a product purchase action method **9000** is depicted. Functions described in the product purchase action method **9000** may be implemented, for example, with HTML pages, XML pages; CGI scripts or programs, servlets or other server-side scripts or programs; client-side scripts, applications or applets, or  
10 active controls; and other client-server methodologies. One of skill having the benefit of this disclosure will appreciate that many known and commercially available electronic commerce systems may be used to perform aspects of the product purchase action method **9000**. Processing in the product purchase action method **9000** initiates at a 'start' terminal **9100** and continues to a 'transaction page(s) communication' procedure **9200** in which pages used to  
15 present the product purchase transaction are communicated to the reproducing apparatus **1300** for rendering on the display **1200**. Upon user input of transaction information a 'secure transaction verification' procedure **9300** verifies transaction information with a transaction security verification mechanism. One of skill in the art will recognize many transaction security verification mechanisms. Conveniently, a predetermined identification number  
20 personal to the user may be used.

Next, a 'merchant communication' procedure **9400** communicates transaction information from the user and product information to a merchant. The merchant may or may not have received sufficient information to complete the transaction depending on the particular requirements of the merchant or transaction. A 'complete transaction' decision  
25 procedure **9500** exits through its 'yes' branch if the 'merchant communication' procedure **9400** returns an indication that the transaction was completed. This is communicated to the user and processing completes through an 'end' terminal **9995**.

If the transaction could not be completed, the 'complete transaction' decision procedure **9500** exits through its 'no' branch and an 'incomplete transaction' output block **9600** reports to the user that the transaction could not be completed at the current time on the basis of the information thus far received. A 'complete now' decision procedure **9700** prompts the user if they wish to complete the transaction now. If so, the 'complete now' decision procedure **9700** exits through its 'yes' branch and a transaction completion' procedure **9800** completes the rest of the transaction. Processing then completes through the 'end' terminal **9995**.

If the user does not wish to complete the transaction at the current time, the 'complete now' decision procedure **9700** exits through its 'no' branch and a 'state information storage' procedure **9900** stores information about the current state of the transaction for later completion by the user. Processing completes through the 'end' terminal **9995**.

Methods according to the invention may be computer implemented either in whole or in part. **Fig. 10** depicts a computer system **10000** capable of embodying aspects of the invention. The action resource provider **1500** may be structures in accordance with the computer system **10000**. The computer system **10000** comprises a microprocessor **10010**, a memory **10020** and an input/output system **10030**. The memory **10020** is capable of being configured to provide a data structure **10040** which may contain data manipulated by the computer system **10000** when embodying aspects of the invention. Further illustrated is a media drive **10070**, such as a disk drive, CD-ROM drive, or the like. The media drive **10070** may operate with a computer-usable storage medium **10075** capable of storing computer-readable program code able to configure the computer system **10000** to embody aspects of the invention. The input/output system **10030** may also operate with a keyboard **10050**, a display **10060**, a pointing device **10090**, a data storage **10045**, or a network such as the data network **1400**. As illustrated, the computer system **10000** is general-purpose computing machinery. As one of skill recognizes programmed instructions may configure general purpose computing machinery to embody structures capable of performing functions in accordance

with aspects of the invention. Special purpose computing machinery including, for example, an application specific integrated circuit (ASIC) may also be used. One skilled in the art will recognize numerous structures of programmed or programmable logic capable of being configured to embody aspects of the invention. In some embodiments, the computer system

5     **10000** is a SPARC-based workstation from Sun Microsystems of Mountain View, CA, running the SOLARIS operating system and the Apache HTTP server with a Secure Sockets Layer module.

In illustrative embodiments of the invention, computer program code configures a computer to embody aspects of the invention. So configured, representations of physical

10    quantities and characteristics are manipulated through a series of operations to achieve aspects of a method, apparatus, and system for providing action selections to an image referencing a product in a video production. One skilled in the art will appreciate the distinction between the manipulation of physical quantities and representations thereof within a computer and will quickly apprehend when reference is being made to one or the other.

15       In some illustrative embodiments, the action resource provider **1500** is a computer system similar to the computer system **10000** and runs an HTTP server. However, one skilled in the art will appreciate that the action resource provider **1500** could be other devices with which the reproducing apparatus **1300** is configured to operate. In the illustrative embodiment the action resource provider **1500** communicates with a data storage **1600**. The

20    data storage **1600** may store, for example, user profile data, product data, merchant data logs, or program guides

User profile data may contain information useful to customizing content and following through on information request, promotion participation, product purchase actions, and other selectable actions. This includes both information explicitly supplied by the user or

25    taken from service registration data, and information derived from the user's pattern of usage. In an illustrative embodiment, explicit data includes name, address, phone number, birthdate,

preferred payment methods, billing address, income, and sex. Usage data may include shows watched, the frequency of performing the different interactive actions, show loyalties, and Web sites visited. A preferred mode of using the user profile data to customize content will conveniently involve first deriving intermediate data. For example, it is simpler to derive an age, or an age group, rather than directly customizing from birthdate. Thus the user profile may include the results of calculations and aggregations of data values to create a smaller and therefore more manageable space of content variations.

### **INDEXICAL CONTENT REFERENCES**

An additional aspect of the invention involves a video production comprising indexical content references. Indexical content references may be beneficially used in conjunction with the zoned system described above, however they are not limited to this use. **Fig. 11** depicts a flow diagram of a method for creating a video production including indexical content references **11000** in accordance with an illustrative embodiment. A video production including an indexical content reference, when reproduced on compatible equipment such as the reproducing apparatus **1300** (described above) engages the equipment to initiate a request to a resource identifier included in the indexical content reference wherein a server addressable via a data network generates a current content reference. Another request is sent to the current content reference and responsive thereto, a response is communicated to the compatible equipment, e.g., the reproducing apparatus **1300**.

Process flow initiates at a 'start' terminal **11100** and continues to an 'indexical reference selection' procedure **11200**. The 'indexical reference selection' procedure **11200** comprises selection of an indexical reference to be encoded in the video production. Selection may be by a human operator or may be automated. Next, processing continues to a 'reference location determination' procedure **11300** that comprises determining the location within the video production where the indexical reference selected by the 'indexical reference selection' procedure **11200** can be encoded. The 'reference location determination'



procedure **11300** may also be performed by a human operator or may be automated. One of skill in the art will recognize many schemes for determining the location within the video production where the indexical reference may be encoded including, for example, time or position-based schemes, and content-based schemes. Additionally, a zone-based scheme may  
5 be used, as described above.

Process flow continues to an 'indexical reference encoding' procedure **11400** that comprises encoding the indexical reference selected by the 'indexical reference selection' procedure **11200** at the location in the video production determined by the 'reference location determination' procedure **11300**. The video production may be in many conventional forms  
10 and conventional video editing equipment known to those skilled in the art may be used to encode the indexical reference. Conveniently, the indexical reference may be encoded in the vertical blanking interval ("VBI") of a conventional analog television broadcast using conventional closed-captioning systems. The Text-2 service of line 21 of the VBI may be used in accordance with CEMA standard EIA-1746 (available from the Electronic Industries  
15 Association ("EIA") of Arlington, VA, U.S.A.). When the video production is in other forms including, for example, digital broadcast or narrowcast video, HDTV, encoded on a tangible medium, or a file for use with a video application, encoding schemes suitable to the form should be used and one of skill in the art will recognize how to encode an indexical reference in accordance with the invention in many conventional forms of distributing the video  
20 production. Process flow completes through an 'end' terminal **11500**.

A video production created according to the method for creating a video production including indexical content references **11000** may be used with other aspects of the invention including, for example, those depicted in **Fig. 1**.

**Fig. 12** depicts a block diagram of the elements in an operating environment of a  
25 system **12000** in accordance with an illustrative embodiment. Corresponding components in

**Fig. 12** are similar to those described above in connection with **Fig. 1** and reference should be made to the portion of the description above

In **Fig. 12**, able to communicate with the reproducing apparatus **1300** via the data network **1400** is a first server **12500** and a second server **12800**, which may communicate, respectively, with a first data storage **12600** and a second data storage **12900**. Generally there need not be functional differences between the first server **12500** and the second server **12800** and accordingly subsequent discussion will be made with reference to the first server **12500** except where additional clarity may be had by reference to the second server **12800**. Further, as one of skill will appreciate, not all embodiments require more than one server, and other embodiments may operate with more than two servers. Additional description of illustrative structures that may implement functions of the first server **12500** is provided in connection with **Fig. 10** above.

In an illustrative embodiment, the first server **12500** is an HTTP server. However, one skilled in the art will appreciate that the first server **12500** could be other devices with which the reproducing apparatus **1300** is configured to operate. In illustrative embodiments the first server **12500** communicates with a first data storage **12600**. The first data storage **12600** may store, for example, user profile data, product data, merchant data logs, or program guides, data objects comprising parameters or parameter values, and data objects comprising data operable with programmed instructions for mapping a first request to a second request.

Referring to **Fig. 3**, in operational mode, the video production communicating device **12100** communicates the video production to the reproducing apparatus **1300**. A trigger interpreter **1330** interprets triggers in the video production and extracts a resource identifier. The trigger interpreter **1330** sends a request **1340** comprising the resource identifier via the data network **12400**.

A server **12380** receives the request **1340**. The server **12380** may be the first server **12500**, the second server **12800**, or another device addressable via the data network **12400**.

The reproducing apparatus **1300** receives a response **1360** via the data network **12400** and a response interpreter **1320** parses and renders the response **1360**. Rendered visual aspects of the response **1360** are sent to a content integrator **1310** which integrates visual aspects of the response **1360** with visual aspects of the video production for communication to the display **12200**.

**Fig. 13** depicts an 'indexical trigger' method **15000** in accordance with an illustrative embodiment. Process flow according to the 'indexical trigger' method **15000** preferably occurs according to programmed instructions executing on networked computing machinery, for example, the first server **12500**. The 'indexical trigger' method **15000** may be implemented with one or more server-side scripts or programs including, for example, JAVA servlets or CGI scripts or programs.

Process flow initiates at a 'start' terminal **15050** and continues to an 'indexical reference request' input block **15100**. The 'indexical reference request' input block **15100** comprises a request to an addressable network resource such as the request **1340**. The request may be compliant with the HTTP protocol in its various versions including, for example, 1.0, draft 1.1, and draft HTTP-NG. It is contemplated that the present invention could also operate with later-developed versions of the HTTP protocol or its successors.

Typically, the request contains, at least, a resource identifier, one or more header field-value pairs which may specify, for example, functional parameters to be used in a client-server session initiated by the request, and a terminator. The resource identifier in the request of the 'indexical reference request' input block **15100** is typically extracted from a trigger. When the request is HTTP compliant, the resource identifier commonly is an uniform resource identifier ("URI") and the one or more header field-value pairs are as specified in the HTTP protocol standard(s).

In some illustrative embodiments, triggers are compliant with CEMA standard EIA-1746 available from The Electronic Industries Association of Arlington Virginia, U.S.A. In

these embodiments, the resource identifier in the trigger is an uniform resource identifier and the uniform resource identifier in the trigger is of the form:

http://<server name>/<videoprod>/<position> (1)

5 The material denoted with angle-brackets <> are quantities used in accordance with the illustrative embodiment. In (1) above, <server name> may be any server addressable on the data network 1400, including, for example, the first server 12500, conveniently, the server may be a dedicated server; <videoprod> refers to an identifier of the video production or a segment thereof into which the trigger is embedded; <position> refers to a position within the video production. Thus, one particular uniform resource identifier according to (1) could be:

10 http://t.b3tv.com/video7/05 (1a)

One of skill in the art having the benefit of this disclosure will appreciate that the present invention is not limited to triggers comprising uniform resource identifiers, and trigger uniform resource identifiers are not limited to the form illustrated in (1) above. One aspect of the present invention is that the resource identifier in the trigger is what is termed  
15 herein “indexical”.

“Indexical” triggers may refer to triggers that comprise a resource identifier including a path to be used by a server in locating an associated resource that is independent (or substantially independent) of the content addressable by the resource identifier. One of skill in the art will appreciate that indexical triggers comprise resource identifiers that are distinct  
20 from the conventional resource identifier used, for example, in connection with World Wide Web sites, where a path specified to be used by a server in locating an associated resource is dependent (or substantially dependent) on the content of resource addressable by the resource identifier. Indeed, is common practice in connection with World Wide Web sites to specify an uniform resource identifier with a path that precisely specifies a path in a file system  
25 where content (for example an HTML page or image) is stored.

One manner in which indexical resource identifiers may be made independent (or substantially independent) from the content addressable by the resource identifier is for the path of the resource identifier to indicate the medium in which the resource identifier is embedded, for example, the path may indicate that the resource identifier is embedded in a video broadcast.

Yet another manner in which indexical resource identifiers may be made independent (or substantially independent) from the content addressable by the resource identifier is for the path of the resource identifier to indicate the broadcast context in which the resource identifier is embedded. For example, the path may indicate a name of a video production and a position in the video production.

One, non-limiting, example of the use indexical trigger resource identifiers is for the <videoprod> to be an identifier of the video production in which the resource identifier is embedded and <position> to refer to an indexed position within the video production. Other examples included, one or more strings which provide only video production information or both video production and position information. Such one or more strings may themselves be easily recognizable as conveying their included information or may be the product of a hash function, transform, and/or other modification which requires data processing to render their information easily recognizable. An additional example of an indexical reference could be as a key for use with a data structure storing key-value pairs on a server. One skilled in the art having the benefit of the teachings herein will quickly appreciate many modifications, variations, and adaptations of indexical triggers as herein described which, while departing from the illustrative examples, remain within the spirit and scope of the present invention as set forth in the appended claims.

An indexical trigger allows enhancing content customization through use of parameterized resource identifiers without consuming limited bandwidth in a video production by providing a generally compact resource identifier which is mapped to a

parameterized resource identifier by a sever, such as the first server **12500**. The server may then redirect the parameterized resource identifier and a response can be communicated to the reproducing apparatus which uses the parameterized resource as a BASE element for further interaction. Further, an indexical trigger allows for time-appropriate enhancing content to be  
5 provided in connection with enhanced video production. A resource identifier in the indexical trigger need not address particular enhancing resources. A server such as the first server **12500**, may contain easily-updatable data comprising time-appropriate enhancing resources. The server may redirect the resource identifier from the indexical trigger to one or more pages providing time-appropriate enhancing resources. Further, an indexical resource  
10 identifier allows for opportunistic provision of enhancing content. An indexical trigger comprising a resource identifier dedicated to opportunistic enhancing content may be embedded in a video production. When it is determined to provide opportunistic enhancing content, it may be done at the server. Still further, indexical triggers may be used to facilitate internationalization of enhancing content. The resource identifier in the trigger, itself, may be  
15 neutral with respect to national or linguistic group. However, a server, the first server **12500** may gain information from header fields and associate expressions in the request about language or location information associated with a viewer or the reproducing apparatus. These may be used by the server to determine an appropriate language in which to respond. A network identifier associated with the reproducing apparatus, e.g. an IP address, may also  
20 be used to identify the country of origin of the requesting hardware and this too, may be used for suitable internationalization with indexical triggers.

Processing of the 'indexical trigger' method **15000** continues to an 'trigger URI parameter extraction' procedure **15150**. The 'trigger URI parameter extraction' procedure **15150** examines the uniform resource identifier in the request **1340** for the values associated  
25 with the <videoprod> or <videoprod> and <position> quantities and extracts this information. Next, a 'trigger URI properties retrieval' procedure **15200** retrieves a first data object comprising first key-value pairs stored in data storage accessible by the server implementing the 'indexical trigger' method **15000**. Using the quantities extracted from the <videoprod> or

<videoprod> and <position> portions of the uniform resource identifier as a key, a 'project lookup' procedure **15250** looks for a value in the first data object associated with the key-- herein termed a "project"--and a 'project properties retrieval' procedure **15300** retrieves and stores a second data object comprising second key-value pairs stored in data storage  
5 accessible by the server implementing the 'indexical trigger' method **15000**.

Next, a 'parameter lookup' procedure **15350** uses a string associated with the parameters as a key with the second key-value pairs to lookup parameters associated with the project. A 'parameter storage' procedure **15400** stores a first parameter in a data structure. Conveniently, the data structure facilitates sorted retrieval, for example, a binary search tree.  
10 A 'remaining parameters' decision procedure **15450** exits through its "yes" branch if additional parameters remain and process flow returns to the 'parameter lookup' procedure **15350** for another iteration of parameter lookup and storage. When no more parameters remain, the 'remaining parameters' decision procedure **15450** exits through its 'no' branch and processing continues to a 'second URI generation' procedure **15500**. The 'second URI  
15 generation' procedure **15500** will be described in greater detail with reference to **Fig. 14** below. Briefly, here, the 'second URI generation' procedure **15500** generates an uniform resource identifier comprising parameter-parameter value pairs.

Processing continues to a 'request redirection' procedure **15600** that receives the uniform resource identifier generated by the 'second URI generation' procedure **15500** and  
20 redirects the request received in the 'indexical reference request' input block **15100** to the second uniform resource identifier generated by the 'second URI generation' procedure **15500**. In some embodiments of the invention the redirection is internal, that is, the redirected request is communicated directly to the server performing the 'indexical trigger' method **15000**. In other embodiments, the redirection is external.

25 Some embodiments employing external redirection communicate a redirect message to the reproducing apparatus **1300** comprising the uniform resource identifier generated by

the 'second URI generation' procedure **15500**. Typically in these embodiments the reproducing apparatus **1300** then sends a redirected request to the second uniform resource identifier.

Other embodiments employing external redirection communicate the redirect message  
5 to a separate server. Such an embodiment can be further illustrated with reference to **Fig. 12**. Initially, the reproducing apparatus **1300** communicates the request received in the 'indexical reference request' input block **15100** via the data network **1400** to, for example, the first server **12500**. Then, the first server **12500** performs steps of the 'indexical trigger' method **15000** and communicates the redirect message to the second server **12800** via the data  
10 network **1400**. The second server **12800** may then perform additional processing responsive to the redirect message including, for example, steps of the 'indexical trigger' method **15000**.

Whether external, internal, or other type of redirection is used in the 'request redirection' procedure **15600**, processing continues to a 'response' output block **15700** that comprises a response sent to the reproducing apparatus **1300**. The response may be, for  
15 example, an HTTP-compliant response message, although other data transfer protocols may be also be used. Processing completes through an 'end' terminal **15800**.

Further detail of the 'second URI generation' procedure **15500** will now be provided with reference to **Fig. 14**. Process flow initiates at a 'start' terminal **15505** and continues to a 'protocol and initial path addition' procedure **15510**. As noted above, in accordance with an  
20 illustrative embodiment, the resource identifier generated by the 'second URI generation' procedure **15500** is an uniform resource identifier. As one of skill in the art recognizes, uniform resource identifiers conventionally begin with a designation of a protocol or scheme to use in attempting retrieval of the identified resource which is followed by one or more elements of a path; accordingly, the 'protocol and initial path addition' procedure **15510**  
25 begins formation of the uniform resource identifier by adding these elements.



Process flow continues to a 'remaining parameters' decision procedure **15520** which determines if parameters remain for addition to the uniform resource identifier and thus controls exit from an iterative block comprising elements described below. Typically during a first iteration of the 'remaining parameters' decision procedure **15520** exits through its 'yes' branch and process flow continues to a 'parameter retrieval' procedure **15530** that retrieves a parameter from the data structure used with the 'parameter storage' procedure **15400**. Next, a 'parameter value' decision procedure **15540** determines if a parameter value associated with that parameter is available. If so, the 'parameter value' decision procedure **15540** exits through its 'yes' branch and a 'parameter value assignment' procedure **15560** assigns a variable the parameter value; if not, the 'parameter value' decision procedure **15540** exits through its 'no' branch and an 'empty string assignment' procedure **15550** assigns the variable the value of the empty string.

Next, a 'pair concatenation' procedure **15570** concatenates the parameter-parameter value pair to the uniform resource identifier. In this step, the parameter and parameter value are separated by an equals sign ("="). Additionally, the 'parameter value assignment' procedure **15560** concatenates a "/" to divide parameter-parameter value pairs. Process flow returns to the 'remaining parameters' decision procedure **15520** to begin another iteration. When sufficient iterations have occurred to retrieve all parameters, the 'remaining parameters' decision procedure **15520** exits through its 'no' branch and process flow continues to an 'initial resource concatenation' procedure **15580**.

Frequently it is desirable for an initial resource comprising references to other resources to be first presented to a user. The 'initial resource concatenation' procedure **15580** facilitates this by concatenating a designator of the initial resource to the path. Process flow completes through an 'end' terminal **15590**

To further aid in understanding the ‘second URI generation’ procedure **15500**, a non-limiting illustration of an uniform resource identifier which could be created in accordance with an illustrative embodiment of the invention is shown by (2) below.

http://<server name>/p/<project>/<name1>=<value1>/<name2>=<value2>/<name3>=/start.html (2)

5           As shown in (2) quantities exemplifying particular aspects of the content URI are shown with angle-brackets <>. In (2), “http://<server name>/p/<project>” illustrates subject matter that could be added by the ‘protocol and initial path addition’ procedure **15510**. Parameters are illustrated by <name1>, <name2>, and <name3>; parameter values are illustrated by <value1>, <value2>, and an empty string following the equals sign which  
10 follows <name3>. An initial resource designator is illustrated by “start.html” as could be added by the ‘initial resource concatenation’ procedure **15580**. As one skilled in the art having the benefit of this disclosure will appreciate, the present invention is not limited to URIs of the length, arrangement, or form (abstractly or concretely) of the exemplary content URI in (2); nor is the present invention limited to URIs generally, rather (2) illustrates an  
15 example of a resource identifier in the form of a URI which could be created by one embodiment among many possible embodiments of the invention which lie within the spirit and scope of the invention as set forth in the appended claims.

Parameters and parameter values may be obtained from header fields and associated expressions in the request received in the ‘indexical reference request’ input block **15100**.  
20 Exemplary header fields used with versions of the HTTP protocol are shown in table 1 below:

Table 1.	
Accept	Range
Accept-Charset	Referer
Accept-Encoding	TE
Accept-Language	User-Agent
Authorization	Content-Encoding
Expect	Content-Language
From	Content-Length
Host	Content-Location
If-Match	Content-MD5
If-Modified-Since	Content-Range
If-None-Match	Content-Base
If-Range	Content-Style-Type
If-Unmodified-Since	Content-Type
Max-Forwards	Date:
Proxy-Authorization	Expires
Last-Modified	Extension-header

In preferred embodiments of the invention, use of header fields and header field values is in compliance with the HTTP protocol available from the World Wide Web Consortium (W3C), Massachusetts Institute of Technology, Laboratory for Computer Science, Cambridge, Massachusetts, U.S.A.

- 5           Parameters may also include information obtained from a network address associated with the reproducing apparatus **1300** including, for example, an IP address. In certain circumstances it could be possible to use this information to determine an approximate geographic location for the reproducing apparatus **1300** which may be correlated to time zones or other geographic information. Geographic or Date field information could be used
- 10          infer a time zone for the reproducing apparatus **1300** initiating the request. Time zone information could then be used in conjunction with an Electronic Program Guide ("EPG") to

gather additional information regarding the video production being viewed by a viewer. Some embodiments of the invention may use parameters based on an EPG alone for creating a response responsive to the broadcast context in which a request was initiated.

Conveniently, parameter-parameter value pairs are added to the content URI by the  
5 'second URI generation' procedure **15500** in alphanumeric order by use of a data structure in the 'parameter storage' procedure **15400** which, when traversed, yields entries in such an order. In an illustrative embodiment parameters are added to the content URI with empty string parameter values when no parameter values are available. Alternative, embodiments omit parameter-parameter value pairs for which no parameter value is available. Still further,  
10 in some embodiments the second resource identifier has neither parameters nor parameter values, while in still other embodiments, the second uniform resource identifier is of other forms including those known in the art.

Parameters relating to a particular viewer or household using the reproducing apparatus **1300** to initiate the request could also be used including, for example, age, gender,  
15 other demographic or psychographic parameters. Additionally, parameters relating to financial information including, for example, known payment instruments for a viewer may also be used. Parameters relating to financial information may be conveniently used in conjunction with applications of the invention to electronic commerce.

In addition, parameters and parameter values may be carried across links by  
20 functionality analogous to using the second URI as an absolute URI that acts as a BASE element for resolving relative URIs in accordance with the HTML specification (available World Wide Web Consortium (W3C), Massachusetts Institute of Technology, Laboratory for Computer Science, Cambridge, Massachusetts, U.S.A.).

## **ENCODING**

Another aspect of the present invention involves a method and system for encoding one or more series of resource identifiers in a video production. **Fig. 15** depicts 'series encoding' system **17000** for encoding one or more series of resource identifiers in a video production. The 'series encoding' system **17000** includes an encoding controller **17100**. The encoding controller **17100** controls aspects of the operation of a video production player **17200**, a resource identifier encoder **17300**, and a video production recorder **17400**. The encoding controller **17100** may be a programmed general purpose computer or may be special-purpose computing hardware.

10       The video production player **17200** communicates a video signal to the resource identifier encoder **17300** under the control of the encoding controller **17100**. In some embodiments the video production player **17200** could be a conventional video cassette player, in other embodiments, the video production player **17200** could be a random access video player, such as a DVD player, or a computer programmed to play a video file.

15       The resource identifier encoder **17300** receives the video signal from the video production player **17200** as an input video signal. The resource identifier encoder **17300** receives instructions from the encoding controller **17100** for embedding resource identifiers in the input video signal. The resource identifier encoder **17300** may be conventional closed-captioning equipment. In some embodiments the resource identifiers could be embedded in  
20       the VBI of a NTSC video signal; in others they could be embedded in a synchronized companion track to the video production. The resource identifier may be portions of triggers according to CEMA standard EIA-1746 or analogous standard.

      The resource identifier encoder **17300** generates an output video signal that comprises the input video signal and resource identifiers embedded therein according to instructions  
25       received from the encoding controller **17100**. The output video signal is communicated to a video production recorder **17400** where it is stored on a video production storage medium

**17500**. The video production recorder **17400** may be, for example, a conventional video cassette recorder, DVD recorder, other device capable of recording a video signal, or device capable of storing a video file. The video production storage medium **17500** is suitably chosen for operation with the video production recorder **17400**.

5           In operation, the 'series encoding' system **17000** may work as follows. A user inputs information to the encoding controller **17100** regarding a series of resource identifiers for encoding in a video production. Next, the encoding controller **17100** determines responsive to the user input positions in the video production at which the resource identifiers should be embedded and appropriate resource identifiers for encoding at those positions. The encoding  
10   controller **17100** sends a signal to the video production player **17200**, the resource identifier encoder **17300**, and the video production recorder **17400** to initiate encoding. The video production player **17200** provides a video signal to the resource identifier encoder **17300**.

          The encoding controller **17100** is able to determine the position in the video production which is being sent from the video production player **17200** to the resource  
15   identifier encoder **17300** at any given moment. The mechanism for achieving this function may vary with the particular video production player **17200**. In some embodiments, the encoding controller **17100** could be provided with the rate of playback the video production player **17200** and the encoding controller **17100** could track playback based on time. In other  
20   embodiments, the video production player **17200** could provide an output signal to the encoding controller **17100** which could be used for tracking. In still other embodiments, the video production player **17200** could provide random access and the encoding controller **17100** could provide the access position.

          When the encoding controller **17100** determines that an appropriate position in the video production has been reached, the encoding controller **17100** sends a signal and the  
25   appropriate resource identifier to the resource identifier encoder **17300**. The resource identifier encoder **17300** embeds the resource identifier in the input video signal received

from the video production player **17200**. An output is generated by the resource identifier encoder **17300** that comprises the input video signal and the embedded resource identifiers which is recorded on a video production storage medium **17500** by the video production recorder **17400**.

5           In an illustrative embodiment the video production storage medium **17500** is a video cassette and the video production played by the video production player **17200** may also be a videocassette. In this embodiment it can be seen that operation of the 'series encoding' system **17000** takes a raw video production played by the video production player **17200** and gives to the raw video production new qualities, properties, and combinations of information.

10       Examples of new properties may include, for example, resource identifiers encoded on the video cassette in one or more particular patterns. Examples of new qualities may include, for example, that when the video cassette is communicated to compatible equipment, the compatible, the resource identifiers configure the compatible equipment to communicate a particular request message to a data network for receipt by, for example, a server. For

15       example, the resource identifier may be seen as instructions that configure a client computing system to perform a particular task, e.g., sending a particular request to a network. In other embodiments the video production storage medium **17500** could be other media suitable for storing a video production.

          The 'series encoding' system **17000** is illustrative of structural elements that may

20       perform steps of a method for encoding one or more series of resource identifiers in a video production. **Fig. 16** depicts a flow diagram of a 'series encoding' method **18000** for encoding one or more series of resource identifiers in a video production in accordance with an illustrative embodiment. For purposes of illustration, reference will be made to elements of the 'series encoding' system **17000** with the understanding that in other embodiments, other

25       suitable structures may perform steps of the 'series encoding' method **18000**.

Process flow initiates at a 'start' terminal **18100** and continues to a 'video production name input' procedure **18200**. The 'video production name input' procedure **18200** provides a query for a name of a video production for encoding. Queries made in the illustrative embodiment of the 'series encoding' method **18000** may be made, for example, to a user or a database. The 'video production name input' procedure **18200** then receives and stores the name. Process flow continues to an 'encoding series start input' procedure **18300** that provides a query for a first starting position for a first series. The first starting position is conveniently input as a time input, for example, 5 minutes from the start of the video production, although a displacement measure or other suitable position identifier could be used in other embodiments.

Process flow continues to an 'encoding series pattern input' procedure **18400**. The 'encoding series pattern input' procedure **18400** provides a query for a first encoding pattern for the first series of resource identifiers. In some embodiments, the first encoding pattern may be a fixed interval so that elements of the first series could be placed in the video production at fixed intervals. In other embodiments a more complex pattern could be used; in some embodiments, a list of entries could be input and would thus provide the first encoding pattern.

Next, an 'encoding series storage' procedure **18500** computes the positions in the video production at which each of the first series of resource identifiers should be embedded and the appropriate resource identifiers for embedding at the positions. As noted, in some embodiments, each of the resource identifiers could be the same. In other embodiments, a portion of the resource identifiers could include a <position> portion relating to the position of the resource identifier in the video production. In still other embodiments a portion of the resource identifier could be a counting index. Many other schemes will be appreciated by one of skill in the art having the benefit of this disclosure within the spirit and scope of the invention as set forth in the appended claims. The 'encoding series storage' procedure **18500** then stores the positions in the video production at which each of the first series of resource



identifiers should be embedded and the appropriate resource identifiers for embedding at the positions.

Next, a 'remaining series' decision procedure **18600** determines whether additional encoding series are desired for addition to the video production. In an illustrative embodiment the 'remaining series' decision procedure **18600** makes this determination by querying a user. If an additional encoding series is desired, the 'remaining series' decision procedure **18600** exits through its 'yes' branch and process flow return to the 'encoding series start input' procedure **18300** to receive a next starting position and a next encoding pattern. When plural encoding series are desired, the 'encoding series storage' procedure **18500** maintains an updated list of elements of the plural encoding series in order that all resource identifiers of the plural encoding series may be embedded in the video production during a single pass through the video production. When no additional encoding series are desired, the 'remaining series' decision procedure **18600** exits through its 'no' branch and process flow continues to an 'encoding initiation' procedure **18700**.

The 'encoding initiation' procedure **18700** initiates the process of embedding the resource identifiers from the one or more encoding series in the video production. The 'encoding initiation' procedure **18700** sends a signal to the video production player **17200**, the resource identifier encoder **17300**, and the video production recorder **17400** that begins the encoding process under the control of the encoding controller **17100** that typically performs the 'encoding initiation' procedure **18700**.

Process flow enters a 'resource identifier encoding' procedure **18800** that detects when a position in the video production is reached where a resource identifier should be embedded. The 'resource identifier encoding' procedure **18800** then provides a signal to the resource identifier encoder **17300** that a resource identifier should be embedded along with the resource identifier. The resource identifier encoder **17300** embeds the resource identifier. An 'encoding complete' decision procedure **18900** determines when all resource identifiers

have been embedded. The 'encoding complete' decision procedure **18900** exits through its 'no' branch and loops back to the 'resource identifier encoding' procedure **18800** while resource identifiers remain to be embedded. When no resource identifiers remain to be embedded, the 'encoding complete' decision procedure **18900** exits through its 'yes' branch and process flow completes through an 'end' terminal **18950**.

It will be appreciated that the 'series encoding' method **18000** could be used to encode both simple and complex patterns of resource identifier in a video production. It may be desirable for identical resource identifiers to be embedded at periodic intervals in a video production; in this way it can be assured that if a viewer joins a video production after the beginning of the video production, they will be presented with the opportunity to retrieve resources available via the resource identifier. It may further be desirable to provide resource identifiers every  $T1$  minutes starting with the  $S1$ 'th minute, for some arbitrary positive  $T1$  and  $S1$ , e.g. every five minutes starting with the second minute of the video production. The 'series encoding' method **18000** may be used to provide such an arrangement by providing the  $S1$ 'th minute in the 'encoding series start input' procedure **18300** and a fixed interval of  $T1$  minutes in the 'encoding series pattern input' procedure **18400**. Similarly it may be desirable for a first series and a second series of resource identifiers to be provided, starting with the  $S1$ 'th and  $S2$ 'th minutes, respectively, and continuing every  $T1$  and  $T2$  minutes, respectively. The 'series encoding' method **18000** may be used to provide such an arrangement by providing the  $S1$ 'th minute and the  $T1$ 'th interval in a first iteration of the 'encoding series start input' procedure **18300** and the 'encoding series pattern input' procedure **18400** and providing the  $S2$ 'th minute and the  $T2$ 'th interval in a second iteration of the 'encoding series start input' procedure **18300** and the 'encoding series pattern input' procedure **18400**. One of skill in the art, having the benefit of this disclosure, will appreciate that arbitrarily complex or numerous encoding patterns may be provided in conjunction with the 'series encoding' method **18000**.

Although the present invention has been described in terms of illustrative embodiments, one skilled in the art will understand that various modifications and alterations may be made without departing from the scope of the invention. Accordingly, the scope of the invention is not to be limited to the particular embodiments discussed herein, but should  
5 be defined only by the appended claims and equivalents thereof.

All patents, patent applications, documents, standards, protocols, and draft protocols referred to herein are incorporated herein by this reference in their entirety.

## Claims

What is claimed is:

1. A method for providing action selections to an image referencing a product in a video production, said method comprising:
  - 5 communicating a video production to a reproducing apparatus, said video production comprising a placement zone and a trigger zone at least partially coincident with said placement zone, wherein said trigger zone comprises a trigger resource identifier, and wherein said placement zone comprises an image referencing a product;
  - 10 communicating to said reproducing apparatus an indication that an action selection interface associated with said product is available in response to a request corresponding to said trigger;
  - communicating to said reproducing apparatus a characterization of said action selection interface, wherein said action selection interface comprises a selectable action.
  - 15
2. The method according to claim 1 further comprising:
  - receiving an indication of the selection of said selectable action;
  - retrieving an action resource associated with said selectable action; and
  - communicating said action resource to said reproducing apparatus.
- 20 3. The method according to claim 1 wherein said video production is communicated over a television network.
4. The method according to claim 1 wherein said video production is distributed in a tangible medium.
5. The method according to claim 1 wherein said video production is transferred over  
25 a computer network.

6. The method according to claim 1 wherein said indication of said action selection interface comprises a visual highlight.
7. The method according to claim 6 wherein said reproducing apparatus is coupled to a viewing device and said visual highlight is communicated to said viewing device only if said reproducing apparatus supports said action selection interface.
8. The method according to claim 1 wherein said selectable action comprises a product purchase action.
9. The method according to claim 1 wherein said selectable action comprises a promotion participation action.
10. The method according to claim 1 wherein said selectable action comprises a information request action.
11. The method according to claim 2 wherein said action resource is selected responsive to a profile of a user associated with said reproducing apparatus.
12. A method for creating a video production including a placement zone and a trigger zone and comprising an image referencing a product and having a selectable action available for communication to a reproducing apparatus, said method comprising:  
selecting a placement zone in a video production, said placement zone comprising an image referencing a product;  
selecting a trigger zone in said video production corresponding to said placement zone;  
embedding a reference in said trigger zone in said video production to an action selection interface, wherein when reproduced on compatible equipment and communicated to a display, a selectable action in said action selection interface is selectable by a viewer.

13. The method according to claim 12 wherein said video production comprises a first track comprising said trigger zone and a second track comprising said placement zone, wherein said first and second tracks are synchronized. 14. Apparatus comprising a processor, a storage, and an input-output system, said apparatus configured for communication with a reproducing apparatus via a data network, programmed instructions configuring said apparatus to perform a method comprising:
- 5 receiving a request from a reproducing apparatus, said request corresponding to a trigger from a trigger zone in a video production communicated to said reproducing apparatus;
- 10 determining whether an action selection interface associated with said request is available; and
- communicating a characterization of said action selection interface to said reproducing apparatus.
- 15 15. A system for providing action selections to an image referencing a product in a video production and operable for use with a reproducing apparatus configured for communication with a display, a data network, and a selection device, comprising:
- 20 a video production communication device, said communicating device communicating a video production comprising a placement zone and a trigger zone to said reproducing apparatus; and
- an action resource provider configured for communication with said reproducing apparatus via said data network, said action resource provider receiving a request from said reproducing apparatus corresponding to a trigger in said trigger zone of said video production, said action resource communicating a characterization of an
- 25 action selection interface to said reproducing apparatus responsive to said request, said action selection interface comprising a selectable action.

16. The system according to claim 15 wherein said action resource provider further:  
receives a request from said reproducing apparatus corresponding to said selectable action;  
retrieves an action resource associated with said selectable action; and  
5 communicates an action resource associated with said selectable action to said reproducing apparatus.
17. A method for providing addressed network content in connection with an enhanced video production and a data network, said method comprising:  
receiving a first request from a reproducing apparatus, said first request  
10 comprising a first resource identifier, said first resource identifier extracted from a video production communicated to said reproducing apparatus;  
determining a second resource identifier responsive to said first resource identifier; and  
redirecting said first request to said second resource identifier, wherein thereafter  
15 a response is communicated to said reproducing apparatus.
18. A method according to claim 17 wherein determining a second resource identifier responsive to said first resource identifier comprises:  
identifying a parameter;  
identifying a parameter value associated with said parameter; and  
20 determining a second resource identifier comprising said parameter and said parameter value responsive to said first resource identifier.
19. A method according to claim 17 wherein determining a second resource identifier responsive to said first resource identifier comprises:  
identifying a parameter of a first type and a parameter of a second type, wherein  
25 said parameter of a first type is identified responsive to a header in said first request; and

identifying a first parameter value associated with said parameter of a first type and a second parameter value associated with said parameter of a second type, wherein said first parameter value is identified responsive to an expression associated with said header.

20. A method according to claim 17 wherein redirecting said first request to said  
5 second resource identifier comprises sending an internal redirect message.

21. A method according to claim 17 wherein redirecting said first request to said second resource identifier comprises sending an external redirect message.

22. A method according to claim 21 wherein said external redirect message is communicated to said reproducing apparatus.

10 23. A system for providing addressed network content in connection with an enhanced video production and a data network comprising:

a video production communication device;

a reproducing apparatus configured to receive video production from said video  
production communication device, said video production comprising a first resource  
15 identifier, said reproducing apparatus communicatively coupled with said data network, said reproducing apparatus further configured to extract said first resource identifier and communicate a first request comprising said first resource identifier via said data network;

a first server communicatively coupled with said data network, said first server configured to perform steps comprising:

20 receiving said first request comprising said first resource identifier;

determining a second resource identifier responsive to said first resource identifier; and

redirecting said first request to said second resource identifier, wherein thereafter a response is communicated to said reproducing apparatus



24. A system according to claim 23 further comprising a second server and wherein said second resource identifier is addressable via said second server.

25. An apparatus comprising a processor, a memory, and an-input output system, programmed instructions configuring said apparatus to provide:

5 a first request receiver for receiving a first request from a reproducing apparatus, said first request comprising a first resource identifier, said first resource identifier extracted from a video production communicated to said reproducing apparatus;

a second resource identifier determiner for determining a second resource identifier responsive to said first resource identifier; and

10 a first request redirector for redirecting said first request to said second resource identifier, wherein thereafter a response is communicated to said reproducing apparatus.

26. An apparatus according to claim 25 wherein the second resource identifier determiner comprises:

a parameter identifier for identifying a parameter;

15 a parameter value identifier for identifying a parameter value associated with said parameter; and

a second resource identifier determiner for determining a second resource identifier comprising said parameter and said parameter value responsive to said first resource identifier.

20 27. An apparatus according to claim 10 wherein the second resource identifier determiner comprises:

a parameter identifier for identifying a parameter of a first type and a parameter of a second type, wherein said parameter of a first type is identified responsive to a header in said first request; and

a parameter value identifier for identifying a first parameter value associated with said parameter of a first type and a second parameter value associated with said parameter of a second type, wherein said first parameter value is identified responsive to an expression associated with said header.

5 28. An apparatus according to claim 25 wherein the first request redirector comprises an internal redirector for sending an internal redirect message.

29. An apparatus according to claim 25 wherein the first request redirector comprises an external redirector for sending an external redirect message.

30. An apparatus according to claim 14 wherein said external redirect message is  
10 communicated to said reproducing apparatus.

31. An apparatus according to claim 25 wherein  
said first request receiver comprises means for receiving a first request from a reproducing apparatus, said first request comprising a first resource identifier, said first resource identifier extracted from a video production communicated to said reproducing  
15 apparatus;

said second resource identifier determiner comprises means for determining a second resource identifier responsive to said first resource identifier; and

said first request redirector comprises means for redirecting said first request to said second resource identifier, wherein thereafter a response is communicated to said  
20 reproducing apparatus.

32. A method for creating a video production including indexical content references, said method comprising:

selecting an indexical reference corresponding to a resource identifier addressable on a data network;

25 determining a reference location in a video production; and

encoding said indexical reference at said reference location in said video production, wherein when said video production is reproduced on a compatible reproducing apparatus, said reproducing apparatus communicates a first request to said resource identifier, a server addressable via said resource identifier generates a current content reference, a  
5 second request is sent to said current content reference, and responsive to said second request information is communicated to said reproducing apparatus..

33. A method for encoding one or more series of resource identifiers in a video production, said method comprising:

receiving a first starting position for a first series;  
10 receiving a first encoding pattern for said first series;  
embedding a first resource identifier at said first starting position; and  
embedding said first series of one or more resource identifiers in said video production in accordance with said first encoding pattern.

34. A method according to claim 33 further comprising:

15 receiving a second starting position for a second series;  
receiving a second encoding pattern for said second series;  
embedding a second resource identifier at said second starting position; and  
embedding said second series of one or more resource identifiers in said video production in accordance with said second encoding pattern.

20 35. A method according to claim 34 wherein said first encoding pattern is a fixed interval.

36. A method according to claim 33 wherein said resource identifiers of said first series are identical.

25 37. A system for encoding one or more series of resource identifiers in a video production comprising:

an encoding controller;

a video production player, operation of said video production player under control of said encoding controller;

5 a resource identifier encoder, said resource identifier encoder configured to receive an input video signal from said video production player, said resource identifier encoder further configured to encode resource identifiers in said input video signal in response to encoding instructions from said encoding controller and provide an output video signal comprising said input video signal and said resource identifiers; and

10 a video production recorder, operation of said video production recorder under control of said encoding controller, said video production recorder receiving said output video signal and storing said output video signal in a storage medium.

1/16




FIG. 1





FIG. 2

2/16

FIG. 3



3/16





FIG. 4

4/16

FIG. 5








FIG. 6A




FIG. 6B

6/16




FIG. 6C





FIG. 6D


7/16


FIG. 7



8/16


FIG. 8






10/16

FIG. 10



11/16

FIG. 11



12/16




FIG. 12







FIG. 13


14/16

FIG. 14




15/16

FIG. 15



16/16

FIG. 16



# INTERNATIONAL SEARCH REPORT

International Application No  
PCT/US 00/00017

## A. CLASSIFICATION OF SUBJECT MATTER

IPC 7 H04N7/173

According to International Patent Classification (IPC) or to both national classification and IPC

## B. FIELDS SEARCHED

Minimum documentation searched (classification system followed by classification symbols)

IPC 7 H04N G06F

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

Electronic data base consulted during the international search (name of data base and, where practical, search terms used)

## C. DOCUMENTS CONSIDERED TO BE RELEVANT

Category *	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
X	WO 97 41690 A (AWARD SOFTWARE INTERNATIONAL I) 6 November 1997 (1997-11-06) abstract page 3, line 35 -page 5, line 15 page 9, line 27 - line 37 page 11, line 22 -page 12, line 36	1-3, 6-10, 12-16,37
X	EP 0 810 790 A (MATSUSHITA ELECTRIC IND CO LTD) 3 December 1997 (1997-12-03)	1-3, 6-10, 12-14,37
A	page 3, column 3, line 39 -page 5, column 7, line 28  ----- -/--	4,5

☒ Further documents are listed in the continuation of box C.

☒ Patent family members are listed in annex.

### \* Special categories of cited documents :

"A" document defining the general state of the art which is not considered to be of particular relevance

"E" earlier document but published on or after the international filing date

"L" document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)

"O" document referring to an oral disclosure, use, exhibition or other means

"P" document published prior to the international filing date but later than the priority date claimed

"T" later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention

"X" document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone

"Y" document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art.

"&" document member of the same patent family

Date of the actual completion of the international search

29 May 2000

Date of mailing of the international search report

06/06/2000

Name and mailing address of the ISA

European Patent Office, P.B. 5818 Patentlaan 2  
NL - 2280 HV Rijswijk  
Tel. (+31-70) 340-2040, Tx. 31 651 epo nl,  
Fax: (+31-70) 340-3016

Authorized officer

Marie-Julie, J-M

## INTERNATIONAL SEARCH REPORT

ational Application No  
PCT/US 00/00017

## C.(Continuation) DOCUMENTS CONSIDERED TO BE RELEVANT

Category *	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
X	WO 98 17064 A (WESTBERG THOMAS E ;KWOH DANIEL S (US); LEUNG ELSIE Y (US); MANKOVI) 23 April 1998 (1998-04-23) page 4, line 37 -page 5, line 14 page 7, line 12 - line 22	1-3,12, 14-16,37
X	WO 97 38529 A (WORLD GATE COMMUNICATIONS L L) 16 October 1997 (1997-10-16)	14-17, 20-25, 28-31,37
A	page 11, line 1 -page 14, line 32 page 25, line 4 -page 26, line 21	1-13,32
X	WO 97 33434 A (EARTH WEB INC ;HIDARY JACK D (US); ACTV INC (US); SPIVACK NOVA T ()) 12 September 1997 (1997-09-12) abstract page 3, line 21 -page 8, line 12	1-3
A	page 11, line 12 -page 14, line 18	14-31
A	US 5 818 935 A (MAA CHIA-YIU) 6 October 1998 (1998-10-06) abstract	1-3
A	US 5 708 845 A (WISTENDAHL DOUGLASS A ET AL) 13 January 1998 (1998-01-13) abstract column 2, line 31 -column 3, line 47	1,6,7
A	EP 0 596 823 A (IBM) 11 May 1994 (1994-05-11) abstract	1,6,7
A	SIMONSON J ET AL: "Version augmented URIs for reference permanence via an Apache module design" COMPUTER NETWORKS AND ISDN SYSTEMS,NL,NORTH HOLLAND PUBLISHING. AMSTERDAM, vol. 30, no. 1-7, 1 April 1998 (1998-04-01), pages 337-345, XP004121413 ISSN: 0169-7552 the whole document	17-36
A	RIO M ET AL: "A framework for broadcasting and management of URIs" COMPUTER NETWORKS AND ISDN SYSTEMS,NL,NORTH HOLLAND PUBLISHING. AMSTERDAM, vol. 28, no. 4, 1 February 1996 (1996-02-01), pages 535-542, XP004002985 ISSN: 0169-7552 the whole document	17-37

# INTERNATIONAL SEARCH REPORT

Information on patent family members

International Application No

PCT/US 00/00017

Patent document cited in search report		Publication date	Patent family member(s)	Publication date
WO 9741690	A	06-11-1997	US 5929849 A CN 1221538 A EP 0896774 A JP 11510978 T	27-07-1999 30-06-1999 17-02-1999 21-09-1999
EP 0810790	A	03-12-1997	CN 1175850 A JP 10112848 A US 5973681 A	11-03-1998 28-04-1998 26-10-1999
WO 9817064	A	23-04-1998	AU 4823197 A BR 9712352 A EP 0932979 A	11-05-1998 31-08-1999 04-08-1999
WO 9738529	A	16-10-1997	US 5999970 A AU 712079 B AU 2724497 A BR 9708551 A CA 2251085 A EP 0893026 A NO 984723 A US 5961603 A	07-12-1999 28-10-1999 29-10-1997 04-01-2000 16-10-1997 27-01-1999 09-12-1998 05-10-1999
WO 9733434	A	12-09-1997	US 5778181 A US 5774664 A AU 2070597 A EP 0885525 A EP 0982943 A US 6018768 A	07-07-1998 30-06-1998 22-09-1997 23-12-1998 01-03-2000 25-01-2000
US 5818935	A	06-10-1998	NONE	
US 5708845	A	13-01-1998	CA 2233444 A EP 0902928 A JP 11512902 T WO 9712342 A	03-04-1997 24-03-1999 02-11-1999 03-04-1997
EP 0596823	A	11-05-1994	US 5539871 A JP 2677754 B JP 7085243 A	23-07-1996 17-11-1997 31-03-1995